



Trends in Neuroscience and Education



journal homepage: www.elsevier.com/locate/tine

# Anodal transcranial direct current stimulation over the left temporoparietal cortex facilitates assembled phonology

Hongli Xue<sup>a,b</sup>, Libo Zhao<sup>c</sup>, Yapeng Wang<sup>a</sup>, Qi Dong<sup>a</sup>, Chuansheng Chen<sup>d</sup>, Gui Xue<sup>a,\*</sup>

a State Key Laboratory of Cognitive Neuroscience and Learning & IDG/McGovern Institute for Brain Research, Beijing Normal University, Beijing 100875, PR China

<sup>b</sup> College of Educational Science, Anhui Normal University, Wuhu 241000, PR China

<sup>c</sup> Department of Psychology, Beihang University, Beijing 100191, PR China

<sup>d</sup> Department of Psychology and Social Behavior, University of California, Irvine 92697, United States

# ARTICLE INFO

Keywords: Artificial language Assembled phonology The left temporoparietal cortex HD-tDCS

# ABSTRACT

A major challenge in learning to read an alphabetic language is to learn to map graphemes to phonemes (i.e., assembled phonology). Previous imaging studies have revealed that the left temporoparietal cortex (LTPC) is associated with assembled phonology. By combining high-definition transcranial direct current stimulation (HD-tDCS) and an artificial language training paradigm, the present study aimed to examine the causal role of LTPC in assembled phonology and tDCS's short- and long-term facilitation effect on reading via assembled phonology. Two matched groups of native Chinese speakers received anodal tDCS either on LTPC or the visual cortex before they were trained to read an artifi

also confirmed in a study that used a parametric design to manipulate word frequency, spelling-sound consistency, imageability, length in letters, bigram frequency, and biphone frequency [31]. A large-scale imaging study has further linked individuals' word decoding ability (a measure of assembled phonology) with their gray matter volume in the LTPC [32]. Finally, many studies have shown that English-speaking children with developmental dyslexia are mainly impaired in assembled phonology and show functional deficits in the LTPC [33–35].

In addition to natural languages, artificial language has also been used to study the neural basis of phonological access and results confirmed the role of the LTPC in assembled phonology [36,37]. In these studies, two groups of subjects were trained to read an artificial language either through addressed or assembled phonology. Functional MRI scans at the end of training revealed greater activation in the LTPC in the assembled than addressed group during both naming and perceptual tasks [37]. They further found that compared to native English speakers, native Chinese speakers were slower at learning assembled phonology and showed weaker activation in the LTPC [36]. This result corroborates previous findings that Chinese readers experience difficulties in assembled phonology when learning to read English [38], and show weaker activation in the LTPC compared to native English speakers when reading English [39].

Although the above studies using fMRI and the artificial language training paradigm have implicated LTPC in assembled phonology, their results were correlational in nature. To substantiate a causal role of LTPC in assembled phonology, it is necessary to use a non-invasive brain stimulation technique such as transcranial direct current stimulation (tDCS) or transcranial magnetic stimulation (TMS) [40,41]. Using tDCS, several studies have found that stimulation on LTPC facilitated language learning [42]. For instance, studies using a statistical learning paradigm found that tDCS on the LTPC facilitated the learning of nonword-picture pairings in healthy subjects [42], and the retrieval of newly-acquired picture names in healthy subjects and participants with aphasia [43]. Using similar tasks and anodal tDCS over five consecutive days, another study revealed beneficial effects on word learning both immediately following stimulation and one week after the last stimulation session [44].

The present study aimed to examine whether LTPC is causally linked to assembled phonology, using an artificial language training paradigm in combination with tDCS. Two matched groups of participants received anodal stimulation either on LTPC or on the control site (the visual cortex, VC) prior to training. Effects on both immediate learning and long-term maintenance several days after training were evaluated. We used High-Definition tDCS (HD-tDCS) with small disk electrodes in 4 × 1 ring configuration, which delivered more focalized stimulation than the conventional tDCS with large rectangular electrodes (mostly 35 cm<sup>2</sup>) [45–50]. We hypothesized that tDCS at LTPC would specifically facilitate learning words via assembled phonology, but not that via addressed phonology. We also expected that the beneficial effect of tDCS would last several days.

#### • • • • • • • •

#### 2.1. Participants

Forty-eight native Chinese speaking college students participated in this study. Data from two participants were incomplete due to computer errors and were deleted. The final sample of 46 participants (22 males) had a mean age of  $19.67 \pm 1.81$  years old, ranging from 18 to 25 years. None of the participants had previous experience with Korean language, from which we created the artificial language (see below). All participants had normal or corrected-to-normal vision, had no previous history of neurological or psychiatric disease, and were strongly righthanded as judged by Snyder and Harris's handedness inventory [51]. The 46 participants were divided into two groups to receive anodal tDCS either on the LTPC or the VC. The two groups were matched on

1						
Background	characteristics	of the	LTPC	and	VC	groups

the second se				
· · · · · · · · · · · · · · · · · · ·	19.61 (1.95)	19.74 (1.71)	24	.81
	11/12	11/12	.00	1.00
	127.43 (5.34)	128.61 (4.62)	79	.43
	75.15 (8.32)	75.43 (7.69)	12	.91
	45.35 (7.35)	45.07 (6.30)	.14	.89
	22.57 (2.39)	22.17 (2.44)	.55	.59

*Note:* Numbers inside the parentheses represent standard deviations. The scores for all tests are the number of correct items. Visual-auditory learning is a subtest of the Woodcock Reading Mastery Tests-Revised (WRMT-R); sight word efficiency and phonemic decoding efficiency are subtests of the Test of Word Reading Efficiency (TOWRE); memory of digits is a subtest of the Comprehensive Test of Phonological Processing (CTOPP).

age, gender, and reading skills in terms of visual-auditory learning as measured by the Woodcock Reading Mastery Tests – Revised (WRMT-R) [52], phonemic decoding efficiency and sight word efficiency as measured by the Test of Word Reading Efficiency (TOWRE) [53], and memory ability as measured by the memory of digits from the Comprehensive Test of Phonological Processing (CTOPP) [54] (Table 1). Informed written consent was obtained from the participants before the experiment. The training and tDCS procedures were approved by the Institutional Review Board of the State Key Laboratory of Cognitive Neuroscience and Learning at Beijing Normal University.

# 2.2. Materials

An artificial language was created based on 144 visual forms of Korean Hangul characters [55]. By pairing these visual forms with auditory word forms in two different ways, we created words to be read in assembled phonology and words to-be-read in addressed phonology. For the former, letters corresponded with phonemes in the international phonetic inventory (IPA), thus following perfect GPC rules. For the latter, there was no correspondence between letters and phonemes, so each of the words had to be read as a whole.

144 artificial language words were created to be read in assembled phonology. Half of these words consisted of two letters (one consonant plus one vowel, i.e., CV) which had either a left-to-right or top-tobottom spatial configuration, the other half of the words consisted of three letters (Consonant-Vowel-Consonant, i.e., CVC) which had an either left-right-bottom or top-middle-bottom configuration (Fig. 1A and B). These words were divided into two sets of 72, with each set being constructed using 12 different Korean Hangul letters, including 6 consonants and 6 vowels. All these phonemes were chosen from the IPA and difficult phonemes were avoided. To confirm our judgment, three native Chinese-speaking graduate students were recruited to rate how easy it is to pronounce these phonemes on a scale of 1 (very difficult to pronounce) to 5 (very easy to pronounce). The average scores were higher than 3 for all phonemes (mean =  $4.43 \pm .78$ ). The words to be read in addressed phonology were created based on those assembled words by shuffling the pairings of the visual word forms and the phonological word forms within each set, thus demolishing the GPC rules. The assignment of the two sets of words to the training conditions was counterbalanced across participants.

For both assembled and addressed words, each set of 72 words was further divided into six matched sub-groups, 12 words in each. For a given participant, one group was used as the target words for training, and the other five groups were used for tests in the five runs (more details in the section of Procedures of Training and Testing). For both training conditions, each subgroup was used equally often as the trained targets across the participants. Across sets and sub-groups, words were matched on the number of strokes (mean =  $6.28 \pm 1.92$ , with a range from 2 to 11), number of units (mean =  $2.50 \pm .50$ , with a



1. Experiment design and examples of the stimuli. (A)Two training conditions were used for participants to receive addressed and assembled phonology training. (B) The word choice test after the learning task in each run. (C) The training schedule. Participants completed the training program after tDCS stimulations on two days, separated by 1 day, and completed the test one week after training.

range from 2 to 3), and spatial structure (left-right vs. top- bottom).

The visual forms of the artificial language words on the computer screen were in  $151 \times 151$  pixels in size, subtending  $1.3^{\circ}$  visual angle. The sounds of these words were read by a native Chinese female speaker. All the sounds were denoised and normalized to the same length (800 ms) and loudness using Audacity 1.2.6 (http://audacity.sourceforge.net).

#### 2.3. Procedures of training and testing

Both the LTPC and VC groups learned both addressed and assembled phonology (Fig. 1A). The training consisted of three sessions, spanning seven days (Fig. 1C). Session 1 (day 1) and Session 2 (day 3) shared identical procedures, consisting of the anodal tDCS being applied at the designated site and four runs of training following the stimulation. The four training runs consisted of two for addressed phonology and two for assembled phonology in an interleaved manner (addressed-assembledaddressed-assembled, or assembled-addressed-assembled-addressed). For both the LTPC and VC groups, the specific ordering of these two training conditions was counterbalanced across participants using an ABBA design. Session 3 (day 7) consisted of post-test only to measure long-term maintenance of the tDCS effect on assembled phonology four days after the last stimulation session.

Each run of training consisted of the learning task and the word choice test (Fig. 1B). The word choice test functioned both as an assessment and facilitator of learning. In each trial of the learning task, the visual form of a word was presented in the center of the computer screen and its pronunciation was presented auditorily through the headphones. Participants were asked to look carefully at the visual word form and listen to its pronunciation. To ensure that participants were awake and attentive, they were instructed to repeat the pronunciation aloud into the microphone. In each of the training trial, the visual word would stay on the screen for 3.5 s, and the next trial would start following a 1-second blank screen.

The requirements on learning differed between the two conditions. In the addressed training condition, participants were asked to memorize each of 12 trained words as a whole. Critically, as mentioned, no GPC rules were implemented in this condition and thus addressed phonology was the only way to read these words. For the assembled training condition, participants were asked to memorize the association between each word and its pronunciation by assembling the pronunciation of each letter in the designated order (left-to-right, top-todown). At the beginning of the experiment, participants were taught explicitly to segment the word's pronunciation into phonemes and then pair each phoneme with the corresponding letter (Fig. 1A), but they were not taught the letters' pronunciations directly.

In the word choice test, each trial consisted of one word auditorily presented through the headphones and four words visually presented from left to right in the center of the computer screen. Participants were asked to indicate which word on the screen matched the sound they heard by pressing one of the four keys (D, F, J, or K) on the keyboard. The visual words would stay on the screen for 4 s, and the next trial would start following a 1-second blank screen. Participants were asked to respond as fast and accurately as they could, and responses made after the visual words disappeared were coded as errors and excluded from the final analysis.

As mentioned before, each run of the word choice test also included one subgroup of untrained words. This was useful for the assembled condition only, in which testing on the untrained words helped evaluate the learning of the GCP rules. Untrained words were also included in the addressed condition, merely for the sake of matching with the assembled condition. However, as such words were not pronounceable in the addressed condition, participants were told that they could make a random response to them in the word choice test. Different subgroups of untrained words were used across the 5 runs to avoid the practice effect in both training conditions.

Stimulus presentation and response collection were programmed using Matlab (Mathworks) with Psychtoolbox 3 extensions (http:// www.psychtoolbox.org/) on an IBM-compatible computer.

# 2.4. tDCS procedure

Two matched groups of participants received anodal tDCS stimulation either on the LTPC or on the VC at the beginning of Session 1 (day 1) and Session2 (day 3) (Fig. 1C). The electric current was constant and delivered by a battery-driven stimulator (Multichannel noninvasive wireless tDCS neurostimulator, Starlab, Barcelona, Spain), which was controlled through a Bluetooth signal. It was adjusted to induce cortical excitability of the target area without any physiological damage to the participants.

Five disk electrodes (11 mm in diameter) submerged in gel were placed in a 4  $\times$  1 high-definition ring configuration [56]. The locations of the stimulation were determined by the international 10–20 EEG electrode placement system, which has been reported to be reliable and successful [57,58].

For the experimental condition, the stimulation site of LTPC was located halfway between T3 and P3 [59,60], around which were the four return electrodes, CP5, CP1, Pz, and PO7 that each took up 25% of

three-way interaction, two-way (stimulation by run) ANOVAs were conducted separately by training condition. For the trained words in the addressed condition, we found a significant main effect of run (F(3,42) = 35.76, p < .001), but neither a main effect of stimulation (F(1,44) = 1.61, p = .21) nor a significant interaction between stimulation and run (F(3,42) = 1.16, p = .33). For the untrained words in the assembled condition, there were significant main effects of stimulation (F(1,44) =

5.52, p = .02) and run (F(3,42) = 3.42, p = .02), and a significant stimulation by run interaction (quadratic, F(3, 42) = 6.66, p = .01). Further paired-sample analysis suggests that the stimulation had significant effects on run 2 (t(44) = -4.04, p < .001) and run3 (t(44) = -2.51, p = .02), but not on run 1 (t(44) = -.31, p = .76) or run 4 (t (44) =

Similar to the results based on RT data, a 2 (stimulation: LTPC, VC)  $\times$  2 (training method: addressed, assembled)  $\times$  4 (run: 1–4) ANOVA on accuracy data showed a marginally significant three-way interaction (F(3,42) = 1.84, p = .09). For the trained words in the addressed condition, there was a significant main effect of run (F(3,42) = 58.99, p < .001), but neither significant main effect of stimulation (F(1,44) = .03, p = .86) nor interaction between stimulation and run (F(3,42) = 1.25, p = .13). For the untrained words in the assembled condition, there were a significant main effect of run (F(3,42) = 68.37, p < .001), and a marginally significant interaction between stimulation and run (F (3,42) = 2.54, p = .06), but no significant main effect of stimulation (F (1,44) = 1.98, p = .17). Further paired-sample analysis suggests that the stimulation had significant effects on run 3 (t(44) = 1.98, p = .05), but not on other runs (all p > .25) (Fig. 3B and D).

# 3.3. LTPC stimulation enhanced long-term maintenance of assembled phonology

2 (stimulation: LTPC, VC)  $\times$  2 (training method: addressed, assembled) mixed ANOVAs were performed for the RT and accuracy data of the word choice test from Session 3. There were significant main effects of stimulation (F(1,44) = 5.34, p = .03) and training method (F (1,44) = 125.54, p < .001), and a marginally significant interaction between stimulation and training method on RT (F(1,44) = 4.69, p =.06). Simple effect analysis further revealed that the LTPC group outperformed the VC group for the untrained words in the assembled condition (t(44) = 2.94, p < .01), but there was no stimulation effect for the trained words in the addressed condition (t(44) = 1.30, p =.20) (Fig. 4A). This result suggests that the LTPC stimulation facilitated the long-term maintenance of the newly acquired assembled phonology. For the accuracy data, there were no significant main effects of stimulation (F(1,44) = 1.77, p = .19) and training method (F(1,44) = 2.45, p = .12), or significant interaction between stimulation and training method (F(1,44) = .51, p = .48) (Fig. 4B).

### 3.4. tDCS effect on the trained words in the assembled condition

Although the trained words in the assembled phonology training condition could not provide unambiguous information due to the possibility of the strategy-shift hypothesis [5,65,66], results from these words were also analyzed for exploratory purposes using a 2 (stimulation: LTPC, VC)  $\times$  4 (run: 1–4) two-way ANOVA. For both dependent measures (the RTs and accuracies of the word choice test), there was a significant main effect of run (all p < .001), but neither main effect of stimulation nor stimulation by run interaction was significant (all

p > .14) (Fig. 3E and F). Although not statistically significant, the pattern of the results was similar to the untrained words. We also tested stimulation difference for the trained words in the assembled condition in Session 3 and found no stimulation differences for either RT or accuracy data (all p > .25) (Fig. 4A and B).

# **L**.../

Using HD-tDCS and an artificial language training paradigm, this study found that anodal stimulation on the LTPC specifically facilitated the test performance of the untrained words in the assembled training condition, but not the trained words in the addressed training condition. These results provide causal evidence for the role of the LTPC in assembled phonology. In addition, the beneficial effect was still present four days after the last stimulation session, indicating that repeated applications of anodal tDCS on LTPC had long-term benefits on assembled phonology.

Our study found clear evidence for the dissociation of assembled phonology and addressed phonology under our training paradigm. First, the outcomes of the two training conditions were only moderately correlated. Second, by calculating the correlations between reading abilities and training results, we found both common and distinct predictors of the two training methods. Visual-auditory learning and sight word efficiency, which reflect general word learning ability, could predict learning performance in both training conditions. In contrast, phonemic decoding efficiency, which reflects word decoding ability [54,67], specifically contributed to learning in assembled phonology.

By combining an artificial language training paradigm and tDCS, the present study had the following strengths. First, the artificial language training paradigm allowed for a strict match of the addressed and assembled training conditions on visual form and phonology, number of repetitions, and overall learning time. Second, the artificial language used in this study included only visual forms and sounds without semantics assigned to the words, which allowed for a comparison of assembled and addressed phonology as pure orthography-to-phonology processes. Third, high-definition tDCS with the stimulation of the visual cortex as a control condition lent strong evidence for a causal role of the stimulated region in the function in question.

Our findings are in line with previous brain stimulation studies that highlighted the role of the LTPC in word learning [41,42,44,68]. It should be noted that the temporoparietal cortex comprises several subregions that are involved in various functions such as attention [60], semantic processing [69], and word decoding [42,70]. However, the low resolution of the conventional tDCS does not allow researchers to separate these functions. Computational modeling studies have

★ . (A) Reaction times and (B) accuracy rates for the three types of words for the LTPC and VC groups for Session 3. TW\_AD = trained words in the addressed condition; UW\_AS = untrained words in the assembled condition; TW\_AS = trained words in the assembled condition. Error bars represent the standard error of the mean.



suggested that the 4  $\times$  1 tDCS montage used here could produce more focal stimulation than could the conventional tDCS [45,48,49]. The use of HD-tDCS might have ruled out the potential confounds of tDCS-related general attention or semantic processing.

More importantly, our study revealed that repeated applications of tDCS on the LTPC could have long-term benefits on assembled phonology. This result is in line with previous studies that examined longterm maintenance of tDCS effects for motor skills [71,72], numerical abilities [73], and language abilities [44,70]. For example, a previous study on aphasia rehabilitation found that gains during tDCS were maintained beyond the end of the training period [70]. Previous studies on skill acquisition suggested that repeated stimulation affected protein synthesis [71], which may serve as the underlying neural mechanism of enhanced long-term maintenance of tDCS effects in the present study and even longer maintenance (i.e., several months) of such effects in other domains [71,73].

The stimulation effect revealed by the present study has important implications for clinical and educational interventions. First, our results suggest that anodal tDCS on LTPC might constitute an effective treatment for deep dyslexia and aphasia that suffer similar grapheme-tophoneme transformation problems. Future studies should directly test the efficacy of anodal tDCS on LTPC in improving reading skills of these clinical groups. Second, our study also suggests a potential way to improve second language learning, particularly for languages with transparent GPC rules. Perhaps such an intervention would reduce the assimilation effect of the native language that tends to hinder second language learning (i.e., Chinese speakers using addressed phonology to learn an alphabetic language) [55,74]. Specifically, previous studies have reported that key regions (i.e., LTPC) for assembled phonology are not involved when reading Chinese [75,76]. One recent study found that Chinese subjects' LTPC (i.e., the left temporal area) was not sufficiently active when reading English [77]. Similarly, it has been found that LTPC (i.e., the left supramarginal gyrus) was less active for Chinese speakers than for English speakers when they used assembled phonology [36]. The results of the present study suggest that anodal tDCS to LTPC may facilitate Chinese speakers' learning of English or other transparent languages.

Our results discussed above revealed a specific effect of LTPC stimulation on untrained assembled words. A similar, but statistically not significant, pattern was found for the trained assembled words. We speculated that with training, assembled words may have undergone the classic shift of reading strategy from assembled phonology to addressed phonology [5,65,66]. In partial support of this speculation, a post hoc analysis found trend of an increased correlation between trained addressed words and trained assembled words from run 1 (r = .20, p = .17) to run 4 (r = .53, p < .001), but a decreased correlation between trained assembled words and untrained assembled words from run 1 (r = .61, p < .001) to run 4 (r = .52, p < .001) (Table 2). These results are consistent with one previous fMRI study by our group that showed direct neural evidence of the strategy shift from assembled to addressed phonology during the process of learning to read an artificial language [37].

Several future research directions should be discussed. First, this study used a between-subject design for the stimulation conditions (but a within-subject design for the training conditions) to avoid the practice effect in artificial language learning. Although we matched the two groups of participants carefully, they might still differ in some aspects, which potentially affected the results of this study. Future studies should use larger samples to confirm the findings in this study. Second, the long-term maintenance of the stimulation effect was only assessed after a delay of several days, so future studies should examine this effect with longer delays. Third, future studies should combine HD-tDCS and functional imaging methods to further elucidate the neural mechanisms of the facilitation effect. Finally, although the miniature artificial language could help to clearly dissociate addressed and assembled phonology, future studies should use natural languages and more intensive training to examine the clinical and educational applications of tDCS.

In conclusion, by combining HD-tDCS and an artificial language training paradigm, the present study revealed a causal role of the left temporoparietal cortex (LTPC) in the learning and long-term maintenance of assembled phonology, but not addressed phonology. These results provide additional evidence for a neural dissociation between these two routes of phonological access, and also have important potential implications for clinical and educational interventions.

# fl . . . . . . . .

The authors declare no competing financial interests.

#### ▲ 11.7 (·. ·I·I.

This work was sponsored by the National Natural Science Foundation of China (31730038), the 973 Program (2014CB846102), the 111 Project (B07008), the Ministry of Education, Humanities and Social Sciences Project (17YJC190027), the Beijing Philosophical and Social Science Foundation (15JYC034), the NSFC and the German Research Foundation (DFG) joint project NSFC 61621136008/DFG TRR-169, and the Guangdong Pearl River Talents Plan Innovative and Entrepreneurial Team grant #2016ZT06S220.

- L.M. Justice, Evidence-based practice, response to intervention, and the prevention of reading difficulties, Lang. Speech Hear. Serv. Sch. 37 (4) (2006) 284–297.
- [2] J.E. Mceneaney, M.K. Lose, R.M. Schwartz, A transactional perspective on reading di

(1) (1999) 205–218.

- [21] J. Levy, C. Pernet, S. Treserras, K. Boulanouar, F. Aubry, J.F. Demonet, P. Celsis, Testing for the dual-route cascade reading model in the brain: an fmri effective connectivity account of an efficient reading style, PLoS One 4 (8) (2009) e6675.
- [22] A. Mechelli, J.T. Crinion, S. Long, K.J. Friston, M.A. Lambon Ralph, K. Patterson, J.L. McClelland, C.J. Price, Dissociating reading processes on the basis of neuronal interactions, J. Cogn. Neurosci. 17 (11) (2005) 1753–1765.
- [23] A. Mechelli, M.L. Gorno-Tempini, C.J. Price, Neuroimaging studies of word and pseudoword reading: consistencies, inconsistencies, and limitations, J. Cogn. Neurosci. 15 (2) (2003) 260–271.
- [24] P.G. Simos, J.I. Breier, J.M. Fletcher, B.R. Foorman, E.M. Castillo, A.C. Papanicolaou, Brain mechanisms for reading words and pseudowords: an integrated approach, Cereb. Cortex 12 (3) (2002) 297–305.
- [25] C. Nosarti, A. Mechelli, D.W. Green, C.J. Price, The impact of second language learning on semantic and nonsemantic first language reading, Cereb. Cortex 20 (2) (2010) 315–327.
- [26] Y. Chen, S. Fu, S.D. Iversen, S.M. Smith, P.M. Matthews, Testing for dual brain processing routes in reading: a direct contrast of chinese character and pinyin reading using fmri, J. Cogn. Neurosci. 14 (7) (2002) 1088–1098.
- [27] S. Fu, Y. Chen, S. Smith, S. Iversen, P.M. Matthews, Effects of word form on brain processing of written chinese, Neuroimage 17 (3) (2002) 1538–1548.
- [28] K. Nakamura, S. Dehaene, A. Jobert, D. Le Bihan, S. Kouider, Subliminal convergence of kanji and kana words: further evidence for functional parcellation of the posterior temporal cortex in visual word perception, J. Cogn. Neurosci. 17 (6) (2005) 954–968.
- [29] Y. Sakurai, T. Momose, M. Iwata, Y. Sudo, K. Ohtomo, I. Kanazawa, Different cortical activity in reading of kanji words, kana words and kana nonwords, Cogn. Brain Res. 9 (1) (2000) 111–115.
- [30] D.H. Thuy, K. Matsuo, K. Nakamura, K. Toma, T. Oga, T. Nakai, H. Shibasaki, H. Fukuyama, Implicit and explicit processing of kanji and kana words and nonwords studied with fmri, Neuroimage 23 (3) (2004) 878–889.
- [31] W.W. Graves, R. Desai, C. Humphries, M.S. Seidenberg, J.R. Binder, Neural systems for reading aloud: a multiparametric approach, Cereb. Cortex 20 (8) (2010) 1799–1815.
- [32] Q. He, G. Xue, C. Chen, Z.L. Lu, Q. Dong, Decoding the neuroanatomical basis of reading ability: a multivoxel morphometric study, J. Neurosci. 33 (31) (2013) 12835–12843.
- [33] E.S. Norton, J.M. Black, L.M. Stanley, H. Tanaka, J.D. Gabrieli, C. Sawyer, F. Hoeft, Functional neuroanatomical evidence for the double-deficit hypothesis of developmental dyslexia, Neuropsychologia 61 (2014) 235–246.
- [34] E. Ripamonti, S. Aggujaro, F. Molteni, G. Zonca, M. Frustaci, C. Luzzatti, The anatomical foundations of acquired reading disorders: a neuropsychological verification of the dual-route model of reading, Brain Lang, 134 (2014) 44–67.
- [35] M.T. Ullman, A neurocognitive perspective on language: the declarative/procedural model, Nat. Rev. Neurosci. 2 (10) (2001) 717–726.
- [36] L. Mei, G. Xue, Z.L. Lu, Q. He, M. Wei, M. Zhang, Q. Dong, C. Chen, Native language experience shapes neural basis of addressed and assembled phonologies, Neuroimage 114 (2015) 38–48.
- [37] L. Mei, G. Xue, Z.L. Lu, Q. He, M. Zhang, M. Wei, F. Xue, C. Chen, Q. Dong, Artificial language training reveals the neural substrates underlying addressed and assembled phonologies, PLoS One 9 (3) (2014) e93548.
- [38] M. Wang, K. Koda, C.A. Perfetti, Alphabetic and nonalphabetic 11 effects in english word identification: a comparison of korean and chinese english l2 learners, Cognition 87 (2) (2003) 129–149.
- [39] L.H. Tan, J.A. Spinks, C.M. Feng, W.T. Siok, C.A. Perfetti, J. Xiong, P.T. Fox, J.H. Gao, Neural systems of second language reading are shaped by native language, Hum. Brain Mapp. 18 (3) (2003) 158–166.
- [40] G. Been, T.T. Ngo, S.M. Miller, P.B. Fitzgerald, The use of tdcs and cvs as methods of non-invasive brain stimulation, Brain Res. Rev. 56 (2) (2007) 346–361.
- [41] G. Hartwigsen, A. Baumgaertner, C.J. Price, M. Koehnke, S. Ulmer, H.R. Siebner, Phonological decisions require both the left and right supramarginal gyri, Proc. Natl. Acad. Sci. USA 107 (38) (2010) 16494–16499.
- [42] A. Floel, N. Rosser, O. Michka, S. Knecht, C. Breitenstein, Noninvasive brain stimulation improves language learning, J. Cogn. Neurosci. 20 (8) (2008) 1415–1422.
- [43] V. Fiori, M. Coccia, C.V. Marinelli, V. Vecchi, S. Bonifazi, M.G. Ceravolo, L. Provinciali, F. Tomaiuolo, P. Marangolo, Transcranial direct current stimulation improves word retrieval in healthy and nonfluent aphasic subjects, J. Cogn. Neurosci. 23 (9) (2011) 2309–2323.
- [44] M. Meinzer, S. Jahnigen, D.A. Copland, R. Darkow, U. Grittner, K. Avirame, A.D. Rodriguez, R. Lindenberg, A. Floel, Transcranial direct current stimulation over multiple days improves learning and maintenance of a novel vocabulary, Cortex 50 (2014) 137–147.
- [45] E.M. Caparelli-Daquer, T.J. Zimmermann, E. Mooshagian, L.C. Parra, J.K. Rice, A. Datta, M. Bikson, E.M. Wassermann, A pilot study on effects of 4×1 high-definition tdcs on motor cortex excitability, Conf. Proc. IEEE Eng. Med. Biol. Soc. 2012 (2012) 735–738.
- [46] A. Datta, V. Bansal, J. Diaz, J. Patel, D. Reato, M. Bikson, Gyri-precise head model of transcranial direct current stimulation: improved spatial focality using a ring electrode versus conventional rectangular pad, Brain Stimul. 2 (4) (2009) 201–207 (207e201).
- [47] A. Datta, M. Elwassif, F. Battaglia, M. Bikson, Transcranial current stimulation focality using disc and ring electrode configurations: fem analysis, J. Neural Eng. 5 (2) (2008) 163–174.
- [48] J.P. Dmochowski, A. Datta, M. Bikson, Y. Su, L.C. Parra, Optimized multi-electrode

stimulation increases focality and intensity at target, J. Neural Eng. 8 (4) (2011) 046011.

- [49] H.I. Kuo, M. Bikson, A. Datta, P. Minhas, W. Paulus, M.F. Kuo, M.A. Nitsche, Comparing cortical plasticity induced by conventional and high-definition 4×1 ring tDCS: a neurophysiological study, Brain Stimul. 6 (4) (2013) 644–648.
- [50] M.A. Nitsche, S. Doemkes, T. Karakose, A. Antal, D. Liebetanz, N. Lang, F. Tergau, W. Paulus, Shaping the effects of transcranial direct current stimulation of the human motor cortex, J. Neurophysiol. 97 (4) (2007) 3109–3117.
- [51] P.J. Snyder, L.J. Harris, Handedness, sex, and familial sinistrality effects on spatial tasks, Cortex 29 (1) (1993) 115–134.
- [52] R. Woodcock, Woodcock Reading Mastery Tests-Revised, American Guidance Service, Circle Pines, MN, 1987.
- [53] W.R. Torgesen J, C. Rashotte, Test of word reading efficiency, Austin, TX: Pro-Ed, 1999.
- [54] T.J. Wagner R, C. Rashotte, Comprehensive test of phonological processing., Austin, TX: PRO-ED, 1999.
- [55] C. Chen, G. Xue, L. Mei, Q. Dong, Cultural neurolinguistics, Prog. Brain Res. 178 (2009) 159–171.
- [56] M.F. Villamar, M.S. Volz, M. Bikson, A. Datta, A.F. Dasilva, F. Fregni, Technique and considerations in the use of 4×1 ring high-definition transcranial direct current stimulation (hd-tdcs), J. Vis. Exp. (77) (2013) e50309.
- [57] A. Rogalewski, C. Breitenstein, M.A. Nitsche, W. Paulus, S. Knecht, Transcranial direct current stimulation disrupts tactile perception, Eur. J. Neurosci. 20 (1) (2004) 313–316.
- [58] B.W. Vines, N.M. Schnider, G. Schlaug, Testing for causality with transcranial direct current stimulation: pitch memory and the left supramarginal gyrus, Neuroreport 17 (10) (2006) 1047